



X-Sense XH-2-M Link+ Pro Heat Sensor

X-Sense XH-2-M Link+ Pro Heat Sensor

Ref: 5906168434976

X-Sense XH-2-M Link+ Pro Heat Sensor

X-Sense XH-2-M Link+ Pro is a reliable thermal sensor that effectively protects your home from fire hazards. With an advanced A1-class thermal resistor and wireless connectivity to other devices, the sensor instantly detects dangerous temperature rises, allowing you to react instantly when they reach dangerous levels. It is ideal for installation in kitchens, garages or other areas where smoke and fumes can occur that would trigger traditional smoke detectors.

Fast and accurate response to heat

Equipped with an A1-class NTC thermistor, the sensor responds to temperature increases between 54-65°C. Unlike standard smoke detectors, the XH-2-M is less prone to false alarms in areas where there is a lot of steam or smoke from cooking, making it an ideal choice for kitchens and garages.

Reliable wireless connectivity

Thanks to Link+ Pro technology, the XH-2-M sensor can be wirelessly connected to other alarms on the network, creating a comprehensive security system for your home. When a single sensor detects a threat, all connected devices will be instantly activated, providing instant warning throughout the building. In total, you can connect up to 24 devices, creating a cohesive security system ideal for large areas.



Two modes of operation

The XH-2-M offers two modes of operation: with and without connection to a base station. Connected to the base station, it offers additional features such as app-based control, while in standalone mode it continues to operate with a 10-year sealed lithium battery that does not need to be replaced. Both modes ensure long-lasting, maintenance-free operation.

Compact design and easy installation

The compact design makes the sensor easily integrate into any interior. Simple installation and operation mean you don't have to worry about complicated installation with additional tools or regular maintenance.

Loud alarm and automatic testing

In case of an emergency, the sensor emits a loud alarm of at least 85 dB, which you can easily hear from anywhere in your home. What's more, the device automatically performs a self-test of its operation, and in the event of a problem, such as low power or a malfunction, it will alert you to intervene, allowing you to avoid interruptions in protecting your home.

Included

alarm unit × 1 mounting bracket × 1 screws × 2 wall plugs × 2 instruction manual × 1

Manufacturer X-Sense Model XH-2-M Link+ Pro Power supply Connected to station: 7-year sealed lithium battery (non-replaceable); Not connected to station: 10-year sealed lithium battery (non-replaceable) Sensor type NTC thermistor Heat sensitivity 129-149°F (54-65°C) Safety standard BS 5446-2:2003 Operating temperature 40-100°F (4.4-37.8°C) Relative humidity ≤ 85% (non-condensing) Alarm volume ≥ 85 dB at 3 m (10 feet) Silence duration Approximately 9 minutes Operating frequency 868 MHz Maximum number of connected units 24 wireless units (compatible with X-Sense Link+ Pro and Link+ sensors)

Price:

€ 23.51

Smart Home, Actuators, Sensors

