



## Digital Universal Multimeter Habotest HT126B

Ref: 5907489608930

Digital Universal Multimeter Habotest HT126B

Habotest HT126B Digital Universal Multimeter

HT126B is a smart and rugged multimeter from Habotest. Distinguished by its precision measurements, you can also use it outdoors. Equipped with a large color display and silicone buttons - it is simple and comfortable to use. Compact and lightweight - it also has a LED flashlight, which allows you to work even in dark places. It requires 4 AAA 1.5 V batteries (not included). You can use it to measure voltage, resistance, capacitance, etc.

### Comfort of use

The multimeter has been designed to give you maximum comfort in use. It is small and handy - its thickness is 25.7 mm. The large display gives you easy access to all important information. In addition, silicone buttons make it easy to use.

### Huge possibilities

The Habotest device is distinguished by incredible precision. It accurately measures AC and DC voltage and current, resistance and capacitance, among other things. You can also check cable activity. With its help you can test diodes, check continuity and true RMS value. It also enables non-contact voltage detection (NCV). Use the arrows to change the mode of the unit, then the LED indicator around the jack input port will light up green.

### User-friendly

That's not the end of the multimeter's benefits. The built-in LED flashlight will provide you with illumination when working in dark rooms. The soft protective case not only protects the unit from damage, but also makes it easy to transport and store. Replacing the HT126B battery is quick and easy, so you won't have any problems.

### Producer

Habotest

### Model

HT126B

### DC voltage measurement range

600mV/6V/60V/600V

### AC voltage measurement range

6V/60V/600V

### DC current measurement range

600mA/10A

### AC current measurement range

600mA/10A

### Resistance measurement range

600 $\Omega$ /6k $\Omega$ /60k $\Omega$ /600k $\Omega$ /6M $\Omega$ /60M $\Omega$

### Capacitance measurement range

6nF/60nF/600nF/6 $\mu$ F/60 $\mu$ F/600 $\mu$ F/6mF/60mF

### Frequency measurement range

6Hz/60Hz/600Hz/6kHz/60kHz/600kHz/6MHz/10MHz

### Measuring range of fill factor

1.0~99.0%

### Temperature ( $^{\circ}$ C/ $^{\circ}$ F)

-40 $^{\circ}$ C ~ 100 $^{\circ}$ C / -40 $^{\circ}$ F ~ 1832 $^{\circ}$ F

### Diode testing

Yes, 0~3V

### NCV

Yes

### Live test

Yes

### Continuity

Yes, <50 $\Omega$

### Number of counts

6000

### Display

VA

### Data storage

Yes

### True RMS value

Yes

### Blown fuse indication function

Yes

### Low battery indicator

Yes

### Automatic power off function

Yes

Input jack port LED indicator

Yes

Illumination

Yes

Flashlight

Yes

Power supply

4x 1.5V AAA battery (not included)

Safety

EN61010-1; CAT III 600V

Weight

Approx. 182 g

Dimensions

Approx. 146 x 72 x 26 mm

Price:

**€ 36.00**

Tools, Measuring tools, Electric meters