











Ref: 6928493306970

Phone: +351962484153

Email: info@mobilemax.pt

(Call to national mobile network)

Charger GensAce IMARS Dual Channel AC200W/DC300Wx2 (White)

Charger GensAce IMARS Dual Channel AC200W/DC300Wx2 (White)

GensAce IMARS Dual Channel AC200W/DC300Wx2 Charger

The GensAce IMARS Dual Channel charger provides dual-channel charging and discharging, and is suitable for many batteries thanks to its wide compatibility. It features a maximum DC charging power of 600W, while the AC200W provides intelligent division of total power. Lightweight and handy, it has an easy-to-read LCD display that provides key information in real time. Its advantages also include low power consumption, an advanced safety system and precise cell balancing.

Many possibilities

The maximum charging power of the device is 100W*2 DC and 300W*2 AC. The product can also be used for discharging, in which case the maximum power is 15W*2. The charger also features a maximum charging current of 15A, provides efficient heat dissipation and has a temperature compensation function. It offers Storage, Balance, ExtDischarge, Digital Power and SyncCharge modes.

Easy-to-read display

The charger is equipped with a practical 2.4-inch LCD display that provides a lot of useful information in real time. This allows you to conveniently check, among other things, the charging or discharging current, operating time or total voltage. Another advantage of the device is its small size (145 \times 76 \times 62 mm) and low weight (530 g), which makes it easy to transport and allows you to use it in many different places.



Compatibility and safety

The GensAce IMARS Dual Channel charger is suitable for charging and discharging LiPo / Li-Ion, LiHV, LiFe 1-6 s and NiMH 1-6 s batteries. It will guickly and safely renew the power source energy of many devices, and you can also discharge the battery to, for example, check its capacity. Also noteworthy are the advanced safety features - the charger has protection against short circuit, overcurrent and overvoltage, among others. It also has the UL94-V0 safety standard.

Phone: +351962484153

Email: info@mobilemax.pt

(Call to national mobile network)

Included

Charger

AC input cable

XT60-T adapter

Adapter XT60-EC5

Adapter XT60-EC3

Manufacturer

GensAce

Name

GensAce IMARS Dual Channel Charger

Model

GEA200WDUAL-EW

Input voltage

AC 100-240V DC 7-30V

Output voltage

DC 1~30V

Maximum input current

DC 30A

Maximum discharge power

15W*2 (main port 6W*2, balance port 9W*2)

Maximum charging power

100W*2 DC 300W*2

Charging current

0.1-15A*2

Discharge current

0.1~3A*2

Cell balancing

1-6 s

USB output

5V / 2.4A

Display type 2.4" IPS LCD

Compatible batteries

LiPo / Li-Ion, LiHV, LiFe 1-6 s, NiMH 1-6 s

Dimensions

145x76x62 mm

Net weight

530 g



F	r	ic	е	:

€ 131.00

Phone: +351962484153

Email: info@mobilemax.pt

(Call to national mobile network)

RC models, Charging, Chargers, 230V