











Ref: 5907489609401

Phone: +351962484153

Email: info@mobilemax.pt

(Call to national mobile network)

Habotest HT125A Digital Universal Multimeter

Habotest HT125A Digital Universal Multimeter

## Habotest HT125A digital universal multimeter

Habotest HT125A digital multimeter is a multifunctional device that will prove useful during electrical work. The product allows you to measure voltage, resistance and many other values. The multimeter has an easy-to-read display that allows you to conveniently read the measurement results, moreover, it is equipped with a flashlight and practical buttons.

## Many useful functions

Habotest HT125A digital universal multimeter is a handy device that surprises with the enormity of its capabilities. It allows to measure with high precision AC and DC voltage, resistance, continuity or frequency, among others. In addition, it offers a Live Test function, enables diode testing, non-contact voltage detection (NCV) and much more. Importantly, the multimeter has practical buttons with which you can efficiently select a function.

## Well designed

Thanks to its small size ( $126 \times 66 \times 19 \text{ mm}$ ), the device fits well in the hand and provides high comfort. It is powered by two AAA batteries (available for sale separately), which you can easily remove and replace. The soft material case is pleasant to the touch, plus it provides effective insulation and is drop-resistant.



Phone: +351962484153

Email: info@mobilemax.pt

(Call to national mobile network)

Included

Digital universal multimeter

Test leads

User's manual

Producer

Habotest

Model

HT125A

HT125B

DC voltage measurement range

400mV/4V/40V/400V/600V

400mV/4V/40V/400V/600V

AC voltage measurement range

4V/40V/400V/600V

AC 4V/40V/400V/600V

Resistance measurement range

 $400 \square /4k \square /40k \square /400k \square /4M \square /40M \square$ 

 $400 \square /4k \square /40k \square /400k \square /4M \square /40Mk \square$ 

Capacitance measurement range

 $4nF/40nF/400nF/4\mu F/40\mu F/400\mu F/4mF$ 

Frequency measurement range

40Hz/400Hz/4kHz/40kHz

40Hz/400Hz/4kHz/40kHz/400kHz/4MHz

Live Test

Yes, sound and light alarm

Yes, sound and light alarm

NCV

Yes, sound and light alarm

Yes, sound and light alarm

Diode testing

Yes, 0∼2V

Yes, 0~2V

Continuity

<50□

<50□

Number of counts

4000

4000

Data storage

Yes

Yes

True RMS value

Yes

Yes

Low battery indicator

Yes

Yes



Automatic power off function
Yes
Yes
Illumination
Yes
Yes
Flashlight
Yes
Yes
Power supply
2x battery 1.5V AAA
2x battery 1.5V AAA
Safety
EN61010-1, CAT III 600V
-
Weight
125 g
-
Dimensions
126 x 66 x 19 mm
-

Price:

€ 15.01

Phone: +351962484153

Email: info@mobilemax.pt

(Call to national mobile network)

Tools, Measuring tools, Electric meters