



## Receiver FlySky-BS6

Receiver FlySky-BS6

Ref: 5905316147515

### FlySky receiver - BS6

It is an indispensable tool for RC model enthusiasts who want to achieve excellent control and reliable connectivity. With 6 PWM channels and advanced AFHDS 2A protocol, it provides stability and precision control in any environment. Its impressive range of 100 to 300 meters on the surface, support for RSSI indicator and compatibility with various power sources make it a versatile solution. Weather resistance, safety certifications and compact size are additional advantages that confirm the BS6's quality and reliability. Let yourself be swept away by technology and precision.

### Stable connection and precise control

FlySky - BS6 receiver is an indispensable choice for any RC model enthusiast who values reliability and excellent quality. With its 6 PWM channels, you have full control over your model's functions, and the advanced AFHDS 2A protocol ensures a stable and interference-free connection.

### Excellent performance in all conditions

Whether you're exploring the terrain or racing around a track, the BS6 receiver provides an impressive range of 100 to 300 meters on the surface. Its single antenna with a range of 180 meters guarantees a reliable and long-range connection, and support for the RSSI indicator allows you to monitor signal strength.

### Multifunctional and compatible

The BS6 receiver operates over a wide voltage range from 4.0V to 6.5V, making it compatible with a variety of power sources. Its PWM data port makes it easy to integrate with a variety of devices and systems, and an online update function provides access to the latest features and fixes.

Robust design, reliability, and safety

Designed to operate in harsh environments, the BS6 receiver can withstand temperatures from -10 °C to + 60 °C and humidity from 20% to 95%. It has CE, RCM and FCC ID: N4ZBS600 certifications that confirm its compliance with international safety and quality standards.

Compact size, easy installation

With minimalist dimensions of 29 x 22 x 16.2 mm and a lightweight design of 7.6 g, this receiver is convenient to install and does not affect the performance of your model.

Product Model:

FS-BS6

PWM channels:

6

Wireless frequency:

2.4GHz

Wireless protocol:

AFHDS 2A

Range:

100 - 300m (ground)

Antenna type:

single antenna (180m)

Power:

4.0-6.5V

RSSI:

Supported

Data port:

PWM

Temperature range:

-10 °C — + 60 °C

Humidity range:

20% -95%

Online Update:

Yes

Dimensions:

29 mm x 22 mm x16,2 mm

Weight:

7.6 g

Certification:

CE, RCM, FCC ID: N4ZBS600

Price:

**€ 23.51**

RC models, Apparatus, Receivers