



Charger SkyRC Ultimate Duo D400 AC/DC

Charger SkyRC Ultimate Duo D400 AC/DC

Ref: 6930460005731

SkyRC Ultimate Duo D400 AC/DC Charger

The charger supports power splitting, which means that the circuit power on channel one can be 300 watts and channel two can be 100 watts, giving a total power of 400 watts. Note that the maximum power of channel two is 200 W, and channel one is 400 W.

Synchronization mode

Synchronization mode allows you to use the same settings for both channels, based on channel one, which significantly saves time in setting up the charger.

DC power supply

The SkyRC Ultimate Duo 400W can be used to power devices that require alternating current (DC). The charger provides 150 watts of power on channel two, converting standard 100-240V AC from a wall outlet to 6-15V DC.

Control from a PC

The user has the ability to monitor the voltage of packs, individual cells and many other functions to which I have a graphical view, thanks to a dedicated application from SkyRC.

Included:

D400 charger

Charging cable x2

Cable with XT60 tip terminated with bananas x2

Power cable

XH adapter x2

User manual

☐ Prodcuent

☐ SkyRC

☐ Model

☐ SK-100123-02

☐ Weight

☐ 2510 g

☐ Max. Charge

☐ 4000 W

☐ Max. Discharge

☐ 2 x 36 W

☐ Current consumption per port max.

☐ 500 mA / cell

☐ Battery voltage

☐ PB 2-24 V

☐ Pulsed charging current

☐ 50-300 mA & OFF

☐ LiPo/LiFe/Lilon/LiHV number of cells charged

☐ 1-7 S

☐ NiMH/NiCd number of charged cells

☐ 1-18 S

Price:

Before: € 182.0031

Now: € 169.00

RC models, Charging, Chargers, 230V + 12V