



Darkflash DR12 ARGB computer fan Darkflash DR12 ARGB computer fan

## Darkflash DR12 ARGB computer fan

The Darkflash DR12 offers speeds from 800 to 1800±10% RPM, airflow of 59.61 CFM and static pressure of 1.29 mm H<sup>2</sup>O. Thanks to its advanced Rifle bearing, the unit provides up to 30,000 hours of quiet and efficient operation. Specially processed blades and anti-vibration rubber seals minimize noise, while the dual illumination ring and ASUS AURA SYNC compatibility allow you to personalize the lighting.

# Performance and speed

The Darkflash DR12 fan offers speeds from 800 to 1800±10% RPM. With such a wide range, the device can adjust its performance to meet different cooling needs, allowing it to effectively cool computer components, regardless of system load.

## Quiet operation

The noise level of the fan ranges from 18 to 90 dBA, so it won't make a nuisance noise. The anti-vibration rubber seals that have been installed on the unit effectively reduce resonance, minimizing noise and ensuring that the computer runs quietly even at higher speeds.

#### Airflow and static pressure

With an airflow of 59.61 CFM and a static pressure of 1.29 mm H<sup>2</sup>O, the Darkflash DR12 guarantees efficient cooling of the computer's

Mobilemax - Gadgets and Accessories Rua Vasco da Gama n61, 8005-411, Estoi - Faro, Portugal (Continente) Telefone: +351962484153 (Chamada para rede móvel nacional) Email: info@mobilemax.pt

Ref: 4710343792765



interior. Specially designed fan blades, whose surface has been smoothed to reduce air resistance, increase air circulation for better cooling performance.

### Rifle bearing

The high-quality Rifle bearing used in the Darkflash DR12 fan provides a service life of up to 30,000 hours. This bearing is characterized by increased durability and quiet operation, which further enhances the comfort of the computer.

## Design and installation

The Darkflash DR12 fan is equipped with a double halo ring, which provides a better cooling and lighting effect. The fan's high-quality frame not only emphasizes the lighting effect, but also guarantees the durability of the design. Assembly of the device is quick and easy. Note: the kit does not include the RC2 PWM controller.

 $\label{localizero} Manufacturer Dark flash Model DR12 Fan speed 800-1800\pm10\% RPM Noise level 18-90 dBAAir flow 59.61 CFM Static pressure 1.29 mm \\ H^2OIntensity 0.30-0.50 ABearing type Rifle bearing MTTF 30,000 hours Dimensions 120 x 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ Manufacturer Dark flash Model DR12 Fan speed 800-1800\pm10\% RPM Noise level 18-90 dBAAir flow 59.61 CFM Static pressure 1.29 mm \\ H^2OIntensity 0.30-0.50 ABearing type Rifle bearing MTTF 30,000 hours Dimensions 120 x 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ H^2OINTENSITY 0.30-0.50 ABearing type Rifle bearing MTTF 30,000 hours Dimensions 120 x 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ H^2OINTENSITY 0.30-0.50 ABearing type Rifle bearing MTTF 30,000 hours Dimensions 120 x 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ H^2OINTENSITY 0.30-0.50 ABearing type Rifle bearing MTTF 30,000 hours Dimensions 120 x 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ H^2OINTENSITY 0.30-0.50 ABearing type Rifle bearing MTTF 30,000 hours Dimensions 120 x 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ H^2OINTENSITY 0.30-0.50 ABearing type Rifle bearing MTTF 30,000 hours Dimensions 120 x 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ H^2OINTENSITY 0.30-0.50 ABearing type Rifle bearing MTTF 30,000 hours Dimensions 120 x 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ H^2OINTENSITY 0.30-0.50 ABearing type Rifle bearing MTTF 30,000 hours Dimensions 120 x 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ H^2OINTENSITY 0.30-0.50 ABearing type Rifle bearing MTTF 30,000 hours Dimensions 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ H^2OINTENSITY 0.30-0.50 ABearing type Rifle bearing MTTF 30,000 hours Dimensions 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ H^2OINTENSITY 0.30-0.50 ABearing 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ H^2OINTENSITY 0.30-0.50 ABearing 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ H^2OINTENSITY 0.30-0.50 ABearing 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ H^2OINTENSITY 0.30-0.50 ABearing 120 x 25 mm Connectors ARGB 5V, PWM 4 pin \\ H^2OINTENSITY 0.30-0.50 ABearing$ 

Preço:

€ 8.50

Telefone: +351962484153

Email: info@mobilemax.pt

(Chamada para rede móvel nacional)

Jogos, Fans, Computer cooling