



IP Indoor Camera ZOSI C528M WiFi 5G Dual 6MP

Ref: 6941709234157

IP Indoor Camera ZOSI C528M WiFi 5G Dual 6MP

ZOSI C528M WiFi 5G Dual 6MP indoor IP camera.

Keep tabs on what's happening at home in your absence. The ZOSI C528M indoor IP camera provides excellent 6MP image quality and a wide range of features, such as automatic motion tracking, to guarantee security and convenience in your home. In addition, you can communicate with your household members thanks to two-way audio support. What's more, the camera is easy to use, and the kit includes the necessary accessories for installation and proper operation of the equipment.

Detailed image in all conditions

The ZOSI C528M camera is equipped with a 6 MP (2304*1296) sensor, which provides crystal clear and detailed images. The 1/3.0" progressive scan CMOS sensor and 4mm lens at F2.0 guarantee excellent detail even in low light. Automatic switching between day and night modes, thanks to its sensitivity to soft light, enables night monitoring up to 10 meters.

Simple control and advanced features

The ZOSI C528M supports dual video transmission, allowing simultaneous transmission of 3MP (2304*1296) and D1 (640*360) quality video. The 1.44-inch screen displays date, time, weather, temperature and humidity. In addition, two-way video calling and automatic motion tracking features make the camera ideal for everyday use in the home.



Peace of mind and protection with smart features

The ZOSI C528M camera uses the H.265 video compression standard, which optimizes the use of bandwidth and recording space. It supports various types of recording, including continuous and alarm recording, and offers local Micro SD card storage (up to 128GB) and cloud storage. Intelligent motion and intrusion detection features and the ability to set up to 5 privacy areas ensure complete security.

Durability and versatility

The camera is powered by a USB-C cable, which you'll find included along with a power adapter. What's more, the ZOSI C528M is rated to operate in temperatures from -10°C to 60°C and humidity up to 95% (non-condensing). In turn, the included components make it easy to mount it on a flat surface, ceiling or wall.

Included

cameramounting basetemplate for mounting the basepower adapter with USB-A to USB-C cablescrews and wall plugsuser manual

ManufacturerZOSIModelC528MCameraPixels6 MP (2304*1296)Image sensor1/3.0" CMOS with progressive scanningLens4 mm at F2.0Lens interfaceM12Luminance thresholdSensitivity to soft light: Switching from day to night mode: 9 luxInfraredx4Warm lightNoneDay / night mode / night viewing distanceICR / 10 mFrame rate15fps, adaptive network transmission frame rateDual transmissionMain transmission: 3MP (2304*1296) sub: D1(640*360)PTZ cameraResolution / image sensor3MP (2304*1296)/1/3.0 "CMOS with progressive scanningLens type / lens interface4.0mm F2.0/M12Minimum illuminationSoft light sensitivity: > 3Lux (daylight mode): < 3Lux (infrared light on)Infrared lights / warm light2 pieces / noneTryb dzienny / nocny / odległość widzenia w nocyICR / 10mPodwójna transmisja15 frames per second, adaptive network transmission frame rateImage settingsMain transmission: 3MP (2304*1296), sub: D1 (640*360)Screen size/resolution1.44 inches /128*128Video compression standardH.265Screen interfaceSPI AWDisplay functionsDate and time display, weather/temperature and humidity display, two-way video connectionsVideo compression standard / bit rateH.265/H.265+ master profile / 32Kbps~2MbpsVideo aspect ratio16:9Privacy area setting / ROISupported (up to 5 areas) / SupportedImage settings / OSD watermarkHD/SD switching support, image duplication / SupportedAudio input/outputBuilt-in speaker with microphoneAudio compression standardSupport for HD/SD switching, image duplicationWhite balance / gain controlG.711ANoise reductionDigital 3DBacklight compensationSupportedWide dynamic rangeSupportedDynamic range / signal-to-noise ratio81dB / 38dBStatus indicatorButton with white circle (Slow flashing: no network, Fast flashing: call/received call, Continuous light: network connection)Signal-to-noise ratio / flashSupported / GD 1GWiFi2.4 GHz/5 GHz EEE 802.11a/b/g/nProtocolTCP/IP, HTTP, DHCP, DNS, MQTT, P2P, ONVIF, RTSPStorageCloud storage with the ability to switch between dual-lens recordingSoftware / max. number of usersZOSI Smart (Android/iOS) AVSS (PC/MacBook) / 5 usersSmart detectionDetection of motion, human, intrusion, etc.Video connectionPress or gesture with a hand movement to call family members at any time for a two-way video callPeople tracking / audioAutomatic people tracking / two-way audioNight vision type / alarmInfrared night visionRecording types / modesContinuous recording, alarm recording Master transmission / slave transmissionOne-button reset / Local memorySupported / Micro SD card (max. 128 GB), NVR cloud storagePower supply / power consumptionDC 5W/2A (type C interface) / 5W MAXSplash protection / installationWaterproof / Flat surface / ceiling / wall mountingOperating temperature and humidity-10°C to 60°C, humidity below 95% (non-condensing)Dimensions152×90×90 mmWeight285g

Preço:

€ 71.00

Casa inteligente, IP cameras

