











Ref: 5907489607827

Telefone: +351962484153

Email: info@mobilemax.pt

(Chamada para rede móvel nacional)

Socket tester with digital display Habotest HT107D

Socket tester with digital display Habotest HT107D

Habotest HT107D socket tester with digital display

Keep your home safe with a socket tester from Habotest. This small and practical device features a digital display and LED indicator that will provide you with the most important information. The device will inform you about the lack of grounding, and it will also enable you to perform RCD test. Thanks to HT107D, you can avoid damage to your equipment and prevent other hazards.

Clear digital display

The tester is equipped with a bright digital display, with which you can easily read the measurement results. The LED indicator located on the top of the device will inform you of any problems. If the tester detects any abnormality, the LEDs will light up in a specific combination. In this way, you will quickly find out, for example, about a correct connection, lack of grounding, live wire, etc. With the HT107D you can also perform a simple RCD test, just by pressing the appropriate button.

Wide application

The Habotest brand device is distinguished by its versatile application. It will prove useful for testing sockets at home, in the office, power strips, wall sockets at school, laboratory, factory, etc. Thanks to its compact design, you can easily store it in your bag or backpack.



Brand

Habotest

Model

HT107D

HT106D

Material

fireproof ABS

fireproof ABS

Voltage range

90 ~ 250V

AC 48-250V

RCD testing

> 30 mA

> 30 mA

Voltage measurement

Yes, $48V \sim 250V / 45 \sim 65 Hz$

Yes, 48-250 V / 45-65 Hz

LCD

Yes

Yes

Backlight

Yes

Yes

Security

EN61010-1, -2-030; EN61326-1, CAT II 300V EN61010-1, -2-030; EN61326-1, CAT II 300V

Dimensions

65 x 62 x 58 mm

65 x 62 x 58 mm

Weight

74g

ok. 50g

Accuracy

 $\pm (2.0\% + 2)$

 $\pm (2.0\% + 2)$

RCD operating voltage

 $220V \pm 20V$

 $220V \pm 20V$

GFCI operating voltage

 $110V \pm 20V$

 $110V \pm 20V$

Working environment

0 °C □ 40 °C, 20% □ 75% RH

0 °C □ 40 °C, 20% □ 75% RH

Storage environment

-10 °C [] 50 °C, 20% [] 80% RH

-10 °C ☐ 50 °C, 20% ☐ 80% RH



u	r	Δ	\sim	Γ
		ㄷ	v.	v.

€ 14.00

Telefone: +351962484153

Email: info@mobilemax.pt

(Chamada para rede móvel nacional)

Ferramentas, Measuring tools, Electric meters