



Habotest HT126A Digital Universal Multimeter

Habotest HT126A Digital Universal Multimeter

Ref: 5907489607810

Habotest HT126A Digital Universal Multimeter

HT126A is a smart and rugged multimeter from Habotest. It is distinguished by its precision measurement, you can also use it outdoors. Equipped with a large display and silicone buttons - it is simple and comfortable to use. Compact and lightweight - it also has a LED flashlight, which allows you to work even in dark places. It requires 4 AAA 1.5V batteries to power it. However, these are not included and must be purchased separately. You can use it to measure voltage, resistance, capacitance, etc.

Convenience of use

Multimeter is designed to provide you with maximum comfort of use. Small and handy - its thickness is 25.7 mm. The large display provides convenient access to all important information. In addition, silicone buttons facilitate the operation of the device.

Great features

The Habotest brand multimeter stands out for its incredible precision. It accurately measures AC and DC voltage and current, resistance and capacitance, among other things. You can also check the activity of cables. With its help you can test diodes, check continuity and true RMS value. It also enables non-contact voltage detection (NCV). Use the arrows to change the mode of the device, then the LED indicator around the jack input port lights up green.

User-friendly

This is not the end of the multimeter's benefits. The built-in LED flashlight will provide you with illumination when working in dark rooms. The soft protective case not only protects the unit from damage, but also makes it easy to transport and store. Replacing the HT126A battery is quick and easy, so you won't have any problems.

Brand

Habotest

Model

HT126A

DC voltage measurement range

600mV / 6V / 60V / 600V

AC voltage measurement range

6V / 60V / 600V

DC current measurement range

600mA / 10A / 6A

AC current measurement range

600mA / 10A / 6A

Resistance measuring range

600 Ω / 6k Ω / 60k Ω / 600k Ω / 6M Ω / 60Mk Ω

Capacitance measurement range

6nF / 60nF / 600nF / 6 μ F / 60 μ F / 600 μ F / 6mF / 60mF

Frequency measurement range

6Hz / 60Hz / 600Hz / 6kHz / 60kHz / 600kHz / 6MHz / 10MHz

Measurement range for the fill factor

1.0 ~ 99.0%

Temperature ($^{\circ}$ C/ $^{\circ}$ F)

-40 $^{\circ}$ C ~ 100 $^{\circ}$ C / -40 $^{\circ}$ F ~ 1832 $^{\circ}$ F

Diode testing

Yes, 0 ~ 3V

NCV

Yes

Live test

Yes

Continuity

& lt; 50 Ω

Diode testing

Yes

Continuity

Yes

Number of counts

6000

Display

TN

Data storage

Yes

True RMS

Yes

Blown fuse indication

Yes

Low battery indicator

Yes

Auto power off

Yes

Jack input port LED

Yes

Backlight

Yes

Flashlight

Yes

Power

4x 1.5V AAA battery (not included)

Security

EN61010-1; EN61326-1 CAT III 600V

Weight

ok. 182 g

Dimensions

146 x 73 x 26 mm

Preço:

€ 26.90

Ferramentas, Measuring tools, Electric meters