



Wall charger, Essager, ECT2CA-JZB01-Z, GaN, USB-A, 2xUSB-C,

Ref: 6971958733262

Wall charger, Essager, ECT2CA-JZB01-Z, GaN, USB-A, 2xUSB-C, 65W (black)

Essager ECT2CA-JZB01-Z GaN USB-A, 2xUSB-C 65W Power Charger (black).

The Essager ECT2CA-JZB01-Z mains charger is a powerful 65W device, ideal for charging a wide range of devices such as laptops, smartphones, tablets and powerbanks. It stands out for its compact size, making it an excellent choice for both home and travel. Using a new generation of GaN (gallium nitride) semiconductor material, the charger is more efficient, smaller and lighter, while offering high performance and stability.

Efficient, fast charging

The GaN technology used in the Essager charger provides fast and efficient charging, minimizing energy loss. With 65 watts of power, it can charge a 13" MacBook Pro up to 75% in about an hour, which is extremely useful during busy work or travel.

Charge your devices conveniently

The Essager ECT2CA-JZB01-Z allows you to charge three devices simultaneously thanks to its USB-A and 2xUSB-C ports. The maximum output power of 65 watts allows you to charge your devices efficiently. Such versatility makes it easy to renew the power of your laptop, smartphone and tablet, for example.

Advanced protection



The Essager ECT2CA-JZB01-Z charger is equipped with numerous protection systems to keep your devices safe. Protection against short-circuit, overheating, overcurrent, electromagnetic field and overcharging guarantees safe charging under various conditions. In addition, the charger is flame resistant, which further enhances its safe use.

Compatibility

The charger supports multiple fast charging protocols, such as PD2.0, PD3.0, PPS, QC4.0 (USB-C) and QC2.0, QC3.0, AFC (USB-A), making it compatible with a wide range of devices, regardless of their make or model. With a universal input voltage of 100-240V, the charger can be used abroad, making it an ideal travel companion.

ManufacturerEssagerModelECT2CA-JZB01-ZColorblackMax. power65 WInterfaceUSB-A, x2 USB-CMaterialABS, PCInput voltage100-240V ~ 50/60 Hz 1.6A Max.Output voltageUSB-C1/2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A (65 W Max.); PPS: 3.3-11V/4.05A, 3.3-21V/3A; USB-A: 5V/3A, 9V/3A, 12V/3A, 20V/3A (60 W Max.).Output powerUSB-C1 + USB-C2: 45 W + 20 W; USB-C1 + USB-A: 45 W + 18 W; USB-C2 + USB-A: 9 W + 9 W; USB-C1 + USB-C2 + USB-A: 45 W + 9 W + 9 WDimensions90.59 x 53.49 x 28.60 mm

Preço:

€ 26.49

Acessórios para telemóveis, Carregadores, mains chargers

