



## SRT-W25 waterproof digital servo with brushless core and high

SRT-W25 waterproof digital servo with brushless core and high voltage

Ref: 6969002002518

### SRT-W25 servo - Reliability and Performance in Any Condition

The SRT-W25 is an advanced waterproof digital servo designed for 1:10 and 1:8 scale RC model enthusiasts, using a high-tension brushless core for superior precision and performance. Its water resistance makes it ideal for rugged off-road or racing applications, offering reliable operation in cars, boats and airplanes alike. The heavy-duty aluminum housing and double-bearing design make the servo extremely durable, while the precision copper and aluminum gears ensure smooth operation.

### Powerful Torque and Precision Operation

The SRT-W25 servo delivers an impressive 23 kg/cm of torque at 6.0V and 25 kg/cm at 7.4V, offering powerful control power even on larger RC models. The speed is 0.16 seconds per 60° at 6.0V and 0.14 seconds per 60° at 7.4V, guaranteeing immediate and precise responses to pilot commands. With adjustable force and speed, the SRT-W25 is perfect for 1:10 and 1:8 scale Trial, Touring, Buggy, Truggy, Monster Truck models, providing full control of the vehicle.

### Complete Assembly Kit and Versatile Use

The SRT-W25 servo comes with a complete mounting kit that includes mounting rubbers, bushings, mounting screws and servo arms, making it easy to install and fit any model. When you choose the SRT-W25, you get a reliable, precise and durable solution that is recognized among professionals and hobbyists around the world, meeting the highest quality standards of the SRT brand.



Included

1x Mounting elastics 4x Bushings 1x Mounting screws 1x Servo arms

Manufacturer Pelikan Model SRT-W25 Type Digital Bearings Dual Gear type Copper and aluminum Operating frequency 330Hz Operating voltage 6.0V - 7.4V Operating temperature range -10 to + 60° Operating speed (6.0V) 0.16 s/60 degrees no load Working speed (7.4V) 0.14 s/60 degrees with no load Torque (6.0V) 23.0 kg/cm Torque (7.4V) 25.0 kg/cm Dimensions 40.7\*20.5\*38.6 mm Weight 72g Cable length 360mm

Preço:

**€ 71.00**

Modelismo, Servos, Standard

