



## X-Sense XC01-R Carbon Monoxide Detector

Ref: 5906168434907

X-Sense XC01-R Carbon Monoxide Detector

### X-Sense XC01-R carbon monoxide detector

The X-Sense XC01-R provides reliable protection against the dangers of this odorless and invisible gas. Using an advanced electrochemical sensor, the device accurately monitors CO concentrations, offering immediate warning when a threat is detected. Equipped with a replaceable CR123A battery, it offers long-lasting performance, and the maximum CO concentration memory function keeps track of peak carbon monoxide levels since the last reset.

### Functional LCD display

The XC01-R sensor has an easy-to-read LCD display that shows the current CO concentration in the room. With LED indicators in three colors (green - power, yellow - failure or low battery, red - alarm), you are always aware of the sensor's operating status.

### Carbon monoxide concentration warning

When a dangerous concentration of carbon monoxide is detected, the sensor sounds an audible alarm of  $\geq 85$  dB. This volume is a guarantee that you won't miss the danger, even while you sleep. So you can be sure that you and the rest of the household are safe.

### Easy installation and convenient use

The X-Sense XC01-R sensor has been designed for easy installation, with screws and mounting studs included, allowing you to quickly



mount the device in the right place. With the test/silence button, you can easily check the sensor's operation or temporarily mute the signal, which is useful in case of false alarms or CO levels falling below the alarm threshold.

10-year service life and replaceable battery

The XC01-R provides a service life of 10 years, eliminating the need for frequent sensor replacement. The R version has a replaceable CR123A battery, which offers flexibility and the ability to use it for longer periods of time, as battery replacement is quick and easy.

Included

X-Sense XC01-R CO sensor x1 Mounting screws x2 Expansion bolts x2 User manual x1

Manufacturer X-Sense Model XC01-R Power supply CR123A or CR2/3A (replaceable battery) Product lifetime 10 years Sensor type Electrochemical Safety standard EN 50291-1:2018 Operating temperature 4.4-37.8°C (40-100°F) Operating humidity 10%-85% RH (non-condensing) Alarm sound level  $\geq$  85 dB at 3 m (10 ft) Storage conditions -20-60°C, 5%-95% RH (non-condensing) Silencing time Approximately 9 minutes

Preço:

**€ 40.50**

Casa inteligente, Actuators, Sensors

