



Habotest HT113 Digital Universal Multimeter

Habotest HT113 Digital Universal Multimeter

Ref: 5907489609432

Habotest HT113 digital universal multimeter

Equip yourself with the lightweight and handy Habotest HT113 digital universal multimeter, which will allow you to conveniently and safely measure voltage, current, resistance and many other values. Habotest HT113 is equipped with a practical stand, so you can put the product on the shelf. Made of soft material, the casing is pleasant to the touch, but also extremely durable, resistant to wear and fall.

A range of functions

The Habotest HT113 digital multi-purpose multimeter offers a number of functions and is perfect for measuring DC and AC voltage, DC current or resistance, in addition, it can test diodes and measure continuity. Special buttons will allow you to conveniently change functions, while the easy-to-read display provides access to the results you need.

Thoughtful design

The device is distinguished by its handy design and weighs only about 220 g. Thanks to the use of soft material, the casing of the device is pleasant to the touch, in addition, it is distinguished by its high resistance to wear and fall. The multimeter is easy to transport and facilitates various types of electrical work, and thanks to the stand you can put it on a table, for example.

Producer

Habotest

Model

HT113

HT113B

HT113C

DC voltage measurement range

200mV/2V/20V/200V/600V $\pm(0,5\%+3)$

400mV/4V/40V/400V/600V $\pm(0,5\%+3)$

600mV/6V/60V/600V $\pm(0,5\%+3)$

AC voltage measurement range

200V/600V $\pm(1,0\%+3)$

400mV/4V/40V/400V/600V $\pm(1,0\%+3)$

600mV/6V/60V/600V $\pm(1,0\%+3)$

DC current measurement range

20mA/ 200mA $\pm(1,2\%+3)$ 10A $\pm(2,0\%+3)$

400uA/4000uA/40mA/400mA $\pm(1,2\%+3)$ 10A $\pm(2,0\%+3)$

600uA/6000uA/60mA/600mA $\pm(1,2\%+3)$ 10A $\pm(2,0\%+3)$

AC current measurement range

-

400uA/4000uA/40mA/400mA $\pm(1,5\%+3)$ 10A $\pm(2,0\%+3)$

600uA/6000uA/60mA/600mA $\pm(1,5\%+3)$ 10A $\pm(2,0\%+3)$

Resistance measurement range

200 Ω /2k Ω /20k Ω /200k Ω /2M Ω /20M Ω $\pm(1,0\%+3)$

400 Ω /4k Ω /40k Ω /400k Ω /4M Ω /40M Ω $\pm(1,0\%+3)$

600 Ω /6k Ω /60k Ω /600k Ω /6M Ω /60M Ω $\pm(1,0\%+3)$

Capacitance measurement range

-

-

10nF/100nF/1 μ F/10 μ F/100 μ F/1mF/10mF $\pm(4,0\%+5)$ 100mF $\pm(5,0\%+5)$

Frequency measurement range

-

-

10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz $\pm(1,0\%+3)$

Measuring range of fill factor

-

-

1%~99% $\pm(3,0\%+3)$

Live Test

No

No

Yes

NCV

No

Yes

Yes

Diode testing

Yes

Yes

Yes

Continuity

Yes

Yes

Yes

Number of counts

2000

4000

6000

Data storage

Yes

Yes

Yes

True RMS value

No

Yes

Yes

Bandwidth

40~400Hz

1kHz

1kHz

Low battery indicator

Yes

Yes

Yes

Automatic power off function

Yes

Yes

Yes

Illumination

Yes

Yes

Yes

Flashlight

No

Yes

Yes

Power supply

2x AAA battery 1.5V

2x AAA battery 1.5V

2x AAA battery 1.5V

Safety

EN61010-2-030 EN61010-2-033 CAT III 600V

EN61010-2-030 EN61010-2-033CAT III 600V

EN61010-2-030 EN61010-2-033CAT III 600V

Weight

Approx. 220 g

Approx. 220 g

Approx. 220 g

Dimensions

151 x 75 x 48 mm

151 x 75 x 48 mm

151 x 75 x 48 mm

Preço:

Antes: € 15.006

Agora: € 9.50

Ferramentas, Measuring tools, Electric meters