



## Transmitter FlySky FS-ST8 + Receiver SR8 - upgraded version

Ref: 5907773230045

Transmitter FlySky FS-ST8 + Receiver SR8 - upgraded version

FlySky FS-ST8 + SR8 transmitter + receiver set

FlySky FS-ST8 + SR8 is equipped with 8-10 channels, and with its omni-directional antenna it prevents interference. It allows you to customize the operation of the control sticks and buttons, and the easy-to-read display will provide the most important information on the operation of the device. Moreover, it is suitable for remote-controlled models of gliders, helicopters, cars, boats, robots, etc.

User-friendly

To use the full potential of FS-ST8 + SR8, you can purchase FlySky C-series sensors, FS-CGPS01 GPS module or CEV04 for channel expansion - then you can use all of them. It is also possible to mount a phone holder (included), for even more convenient use. What's more, the product supports FlySky Assistant 3.0, which will allow you to perform device updates and store/copy files.

Thoughtful design

The device uses altitude, speed, temperature and voltage sensors. It will also provide RSSI reverse transmission, BVD voltage and other telemetry information. What's more, the FS-ST8 + SR8 features an ergonomic design, so you can use it comfortably. Meanwhile, the transparent elements make the RGB backlighting more visible - and you can also personalize it.

Efficient power supply

The FS-ST8 + SR8 can be powered by AA/2S batteries or 4 x 1300 mAh NiMH rechargeable batteries that stand out for their low power consumption and run for up to 10 h on a single charge. Enjoy the possibilities that FlySky offers. Attention: neither batteries AA nor NiMH batteries are not included in the package.

Included  
transmitter  
receiver  
BVD battery voltage detection line  
JR RF adapter  
phone holder  
mounting elements for throttle adjustment  
mounting elements for throttle with reverse sensor  
mounting elements for FS-FAR01 2.4G external antenna  
user manual  
Manufacturer  
FlySky  
Model  
FS-ST8 + SR8  
Color  
black  
Number of channels  
8-10  
Wireless frequency  
2.4 GHz ISM  
Transmission power  
<20 dBm  
Wireless protocol  
ANT  
Range  
>1000m (AIR)  
Channel resolution  
4096  
Rechargeable battery  
1.5AA \* 4 or 2S (JST)  
Low voltage alarm  
□4.2 V/7.2 V  
Antenna type  
Dual antennas  
Display  
LCD 128 x 64  
Data port  
DSC, Type C  
Temperature range  
-10 °C - + 60 °C  
Humidity range  
20% -95%  
Online update  
Yes

Dimensions

176 x 210.9 x 82.5 mm

Weight

420 g

Certifications

CE, FCC ID: N4ZST800

Preço:

**€ 105.01**

Modelismo, Apparatus, Transmitters, Air transmitters