



True RMS Digital Universal Multimeter Habotest HT112B

Ref: 5907489606677

True RMS Digital Universal Multimeter Habotest HT112B

Habotest HT112B multimeter

HT112B is an ultra-thin, next-generation smart multimeter. Equipped with a large 2.88" display and silicone buttons - it is simple and comfortable to use. It provides precise measurement of various parameters. Compact and lightweight - it also has a LED flashlight that allows you to work even in dark places. For its power supply it requires 2 CR2302 3V batteries.

Perfectly thought-out design

This practical multimeter was designed to provide you with maximum comfort of use. Small and handy - its thickness is only 1.9cm. The 2.88" display will provide you with convenient access to all important information. Large, silicone buttons make it easy to use the device.

Great features

The Habotest brand multimeter stands out for its incredible precision. It accurately measures AC and DC voltage, resistance and capacitance, among other things. It also recognizes cable activity. With its help you can test diodes, check continuity and true RMS value. It also enables non-contact voltage detection (NCV). HT112B features intelligent operation and ACV auto-detection.

User-friendly

This is not the end of the multimeter's benefits. The built-in LED flashlight will provide you with bright illumination when working in dark

rooms. The soft protective case not only protects the unit from damage, but also makes it easy to transport and store. Replacing the HT112B battery is child's play - it won't cause you any problems.

Brand

Habotest

Model

HT112A

HT112B

DC voltage measurement range

2V/30V/200V/600V $\pm(0.5\%+3)$

60mV/600mV/6V/60V/600V $\pm(0.5\%+3)$

AC voltage measurement range

2V/30V/200V/600V $\pm(1.0\%+3)$

60mV/600mV/6V/60V/600V $\pm(1.0\%+3)$

DC current measurement range

20mA/200mA/600mA $\pm(1.2\%+5)$

6000uA/60mA/600mA $\pm(1.2\%+5)$

AC current measurement range

20mA/200mA/600mA $\pm(1.5\%+5)$

6000uA/60mA/600mA $\pm(1.5\%+5)$

Resistance measurement range

200 Ω /2k Ω /20k Ω /200k Ω /2M Ω /20M Ω $\pm(1.0\%+5)$

600 Ω /6k Ω /60k Ω /600k Ω /6M Ω /60M Ω , $\pm(1.0\%+5)$

Capacitance measurement range

Not applicable

6nF/60nF/600nF/6 μ F/60 μ F/600 μ F/6mF/60mF $\pm(4.0\%+5)$

Frequency measurement range

Not applicable

10Hz/100Hz/1000Hz/10kHz/100kHz/1000kHz/10MHz $\pm(1.0\%+5)$

Duty measurement range

Not applicable

1%~99%, $\pm(3.0\%+5)$

Counts

2000

6000

Auto/manual range

Automatic

Automatic

SMART function

Yes

Yes

Auto recognition of probe inserted into current input

Yes

Yes

Live test

Yes

Yes

NCV

Yes

Yes

Diode test

Yes

Yes

Continuity

Yes

Yes

Data hold

Yes

Yes

True RMS

Yes

Yes

Blown fuse indication

Yes

Yes

Low battery indicator

Yes

Yes

Autopower off

Yes

Yes

Backlight

Yes

Yes

Flashlight

Yes

Yes

Power supply

2x CR2032 3V battery (included)

2x CR2032 3V battery(included)

Safety

EN61010-2-030; EN61010-2-033, EN61326-1 CAT III 600V

EN61010-2-030; EN61010-2-033, EN61326-1 CAT III 600V

Preço:

€ 27.50

Ferramentas, Measuring tools, Electric meters