



Digital Universal Multimeter Habotest HT112A True RMS

Ref: 5907489606660

Digital Universal Multimeter Habotest HT112A True RMS

Habotest HT112A digital multimeter

HT112A is an ultra-thin, next-generation smart multimeter. Equipped with a large display and silicon buttons, it is easy and comfortable to use. It provides precise measurement of various parameters. Compact and lightweight - it also has a LED flashlight, which allows you to work even in dark places. For its power supply it requires 2 CR2032 3V batteries.

Perfectly thought-out design

This practical multimeter was designed to provide you with maximum comfort of use. Small and handy - its thickness is only 1.9cm. The easy-to-read display will provide you with convenient access to all important information. Large, silicone buttons make it easy to use the device.

Great possibilities

The Habotest brand multimeter stands out for its incredible precision. It accurately measures AC and DC voltage, resistance and current, among other things. It also recognizes cable activity. With its help you can test diodes, check continuity and true RMS value. It also enables non-contact voltage detection (NCV). The HT112A also has a SMART function that provides intelligent detection.

User-friendly

Mobilemax - Gadgets and Accessories

Rua Vasco da Gama n61, 8005-411, Estoi - Faro, Portugal
(Continente)

Telephone: +351962484153
(Chamada para rede móvel nacional)
Email: info@mobilemax.pt

This is not the end of the multimeter's benefits. The built-in LED flashlight will provide you with bright illumination when working in dark rooms. The soft protective case not only protects the unit from damage, but also makes it easy to transport and store. Replacing the HT112A battery is child's play - you won't have any problems.

Brand

Habotest

Model

HT112A

HT112B

DC voltage measurement range

2V/30V/200V/600V $\pm(0.5\%+3)$

60mV/600mV/6V/60V/600V $\pm(0.5\%+3)$

AC voltage measurement range

2V/30V/200V/600V $\pm(1.0\%+3)$

60mV/600mV/6V/60V/600V $\pm(1.0\%+3)$

DC current measurement range

20mA/200mA/600mA $\pm(1.2\%+5)$

6000uA/60mA/600mA $\pm(1.2\%+5)$

AC current measurement range

20mA/200mA/600mA $\pm(1.5\%+5)$

6000uA/60mA/600mA $\pm(1.5\%+5)$

Resistance measurement range

200 Ω /2k Ω /20k Ω /200k Ω /2M Ω /20M Ω $\pm(1.0\%+5)$

600 Ω /6k Ω /60k Ω /600k Ω /6M Ω /60M Ω , $\pm(1.0\%+5)$

Capacitance measurement range

Not applicable

6nF/60nF/600nF/6 μ F/60 μ F/600 μ F/6mF/60mF $\pm(4.0\%+5)$

Frequency measurement range

Not applicable

10Hz/100Hz/1000Hz/10kHz/100kHz/1000kHz/10MHz $\pm(1.0\%+5)$

Duty measurement range

Not applicable

1%~99%, $\pm(3.0\%+5)$

Counts

2000

6000

Auto/manual range

Automatic

Automatic

SMART function

Yes

Yes

Auto recognition of probe inserted into current input

Yes

Yes

Live test

Yes

Yes

NCV
Yes
Yes
Diode test
Yes
Yes
Continuity
Yes
Yes
Data hold
Yes
Yes
True RMS
Yes
Yes
Blown fuse indication
Yes
Yes
Low battery indicator
Yes
Yes
Autopower off
Yes
Yes
Backlight
Yes
Yes
Flashlight
Yes
Yes
Power supply
2x CR2032 3V battery (included)
2x CR2032 3V battery (included)
Safety
EN61010-2-030; EN61010-2-033, EN61326-1 CAT III 600V
EN61010-2-030; EN61010-2-033, EN61326-1 CAT III 600V

Preço:

€ 19.50

Ferramentas, Measuring tools, Electric meters