



Servo Digital SRT DL3020 DC WATERPROOF (20 kg-0,11s/60°)

Servo Digital SRT DL3020 DC WATERPROOF (20 kg-0,11s/60°)

Ref: 6969003002012

KEY FEATURES

Ideal for 1/10 on road and 1/8 off road scale applications, as well as large scale airplanes and jets
incredible efficiency and low power consumption

2 µsec Dead Band

Type

Digital

Bearing

Double

Motor type

DC

Gear type

Metal

Gearbox material

Copper and aluminum

Control system

Pulse width control

- Operating frequency
- 1520µs / 330hz
- Operating voltage
- Dc4.8-6.0v
- Operating temperature range
- -10 to + 60 degrees
- Operating speed (4.8v)
- 0.13 sec/60 degrees at no load
- Operating speed (6.0v)
- 0.11 sec/60 degrees with no load
- Stall torque (4.8v)
- 18.0kg.cm (250.0 oz/in)
- Stall torque (6.0v)
- 20.0kg.cm (277.7 oz/in)
- Potentiometer drive
- Direct drive
- Dimensions
- 40.7x20.5x39.5 mm /1.6x0.8x1.55 in
- Weight
- 56.0g (1.98 oz)
- Length of connecting cable
- Jr 250 mm

Preço:

€ 28.50

Modelismo, Servomechanisms, Standard