



Digital Anemometer Habotest HT625A

Digital Anemometer Habotest HT625A

Ref: 5907489606769

Habotest HT625A anemometer

HT625A is a functional anemometer with high sensitivity. It is equipped with an 8-blade rotor and HD color display. It is powered by 3 AAA 1.5V batteries. It allows measurements in different units. Lightweight, handy and portable - it will surprise you with its simple and convenient operation.

Precise measurement of various parameters

This multifunctional anemometer accurately measures air flow velocity and volume, as well as air channel area. It is distinguished by its high sensitivity. It also allows you to make average measurements. You can access the various functions and settings by pressing certain buttons.

Selectable unit

Habotest meets the needs of users around the world. The ability to change the unit of measurement will allow you to tailor the performance of the device to your needs and habits. Options include m/s, km/h, miles/h, ft/s, and even knots.

Practical, portable, convenient to use

Anemometer is equipped with a clear, color HD display. It provides convenient access to the most important information related to the



operation of the device. Thanks to it you can quickly check not only the measurement results, but also, for example, battery status. HT625A is also lightweight and portable. Using it is extremely comfortable. It fits perfectly in your hand and does not cause any discomfort. Transporting it is not a problem either - you can easily fit it into a bag and take it anywhere you need it.

Brand

Habotest

Model

HT625A

HT625B

Air speed measurement range, resolution and accuracy

0.4-30m/s: 0.01, $\pm(2\%+0.5\text{m/s})$;1.40-108km/h: 0.01-0.1, $\pm(2\%+1.8\text{km/h})$;1.30-98.50ft/s: 0.01, $\pm(2\%+1.6\text{ft/s})$;0.80-58.30 knots: 0.01, $\pm(2\%+1.0\text{ knots})$;0.90-67.10mph: 0.01, $\pm(2\%+1.1\text{mph})$;78.00-5900ft/m: 0.01-0.1, $\pm(2\%+10\text{ft/m})$

0.4-30m/s: 0.01, $\pm(2\%+0.5\text{m/s})$;1.40-108km/h: 0.01-0.1, $\pm(2\%+1.8\text{km/h})$;1.30-98.50ft/s: 0.01, $\pm(2\%+1.6\text{ft/s})$;0.80-58.30 knots: 0.01, $\pm(2\%+1.0\text{ knots})$;0.90-67.10mph: 0.01, $\pm(2\%+1.1\text{mph})$;78.00-5900ft/m: 0.01-0.1, $\pm(2\%+10\text{ft/m})$

Air volume measurement range, resolution

0-9999 CFM (CMM, CMS), 0.01-0.1

0-9999 CFM (CMM, CMS), 0.01-0.1

Display

9999 counts with a bargraph

9999 counts

Air temperature, resolution, accuracy

Not applicable

-20°C-60°C (-14°F-140°F), 0.1, $\pm 1.5^\circ\text{C}$

Dew point temperature, resolution, accuracy

Not applicable

-20°C-60°C (-4°F-140°F), 0.1, $\pm 1.5^\circ\text{C}$

Wet bulb temperature, resolution, accuracy

Not applicable

-50°C-60°C (-58°F-140°F), 0.1, $\pm 1.5^\circ\text{C}$

Air humidity, resolution, accuracy

Not applicable

0-99%, 0.1, $\pm 4^\circ\text{C}$

USB

No

Yes

Air duct area settings

Yes

Yes

Data hold

Yes

Yes

MAX/MIN/AVG

Yes

Yes

Auto power off

Yes

Yes

Low battery indication



Yes

Yes

Power supply

3x AAA 1.5V batteries (included)

3x AAA 1.5V batteries (included)

Weight

About 180g

About 180g

Dimensions

197x60x33mm

197x60x33mm

Preço:

€ 37.00

Ferramentas, Measuring tools, Electric meters

