



**Rechargeable Battery AGM VRLA Green Cell AGM10 12V 20Ah (for Rechargeable Battery AGM VRLA Green Cell AGM10 12V 20Ah (for lawn mower, boat, motor, cart)**

Ref: 5902701411565

Green Cell AGM VRLA Maintenance-free AGM Battery AGM10 12V 20Ah (for lawnmower, boat, scooter, cart).

What is an AGM battery? AGM is an energy storage battery with a wide range of commercial applications. Not only can we power toys and alarm systems with it, but it is also the heart of any UPS. Green Cell AGM batteries have a very wide range of applications. They can be used for both cyclic and buffer operation.

**Cyclic operation**

The cyclic use of a battery is to use it as a stand-alone power source. AGMs of this type are prepared for very frequent charging and discharging. Thus, they are used in wheelchairs, photovoltaic installations, golf carts, toys and lawnmowers.

**Buffer operation**

Buffer operation allows a battery to act as a backup power supply for a plugged-in device. A battery connected to a power system in the event of a failure of the main power source provides additional power. They are used in this way in alarm systems, UPS, cash registers or emergency lighting.

**Maintenance-free operation**

Batteries made with AGM technology were created to ensure the greatest possible safety during use. Thanks to the self-regulation

function (VRLA valves), AGMs provide up to 5 years of maintenance-free operation. It increases the safety of the device's operation, regardless of the position of the battery.

#### Safety

AGM batteries are designed for even the most extreme conditions. The fiberglass used ensures that the electrolyte is sealed in the casing which allows the battery to be used in any position without fear of spilling the contents. This is especially important in the case of powered toys, which are exposed to various types of shocks. This makes Green Cell AGM batteries completely safe for users.

□Manufacturer.

□Green Cell

□Model

□AGM10

□Capacity

□20 Ah

□Voltage

□12 V

□Type

□VRLA AGM

□Terminal

□M5 screw (F3)

□Max. discharge current

□3C

□Capacity by temperature

□(40 °C~102%) (25 °C~100%) (0 °C~85%) (-15 °C~65%)

□Cyclic charging

□14.5 - 14.9 V (-30 mV/C)

□Maximum charging current

□6.0 A

□Lifetime

□more than 5 years

□Self-discharge

□2% per month (at 25°C)

□Buffer charging

□13.5 - 13.8 V (-20 mV/C)

□Internal resistance

□≤16.2mΩ (at temp. 25°C)

□Capacity range

□10 - 20 Ah

□Weight

□5.20 kg

□Dimensions

□181 x 77 x 167 mm

Preço:

**€ 42.50**

Acessórios para computadores, Other